

Stratos Evo A402 CC Transmitter Specific HART Command Specification

using the HART® Communications Protocol

Document Revision: 2.1

Device Number: 0xD1

Device Revision: 4

Knick Elektronische Messgeräte GmbH & Co. KG

HART is a registered trademark of the HART® Communication Foundation of Austin, Texas, USA.

1 1. Reference Documents

| Document Title | Revision | Document Number |
|---|----------|-----------------|
| HART® - FSK Physical Layer Specification | 8.1 | HCF_SPEC-54 |
| HART® - Data Link Layer Specification | 8.0 | HCF_SPEC-81 |
| HART® - Command Summary Specification | 8.1 | HCF_SPEC-99 |
| HART® - Universal Command Specification | 6.0 | HCF_SPEC-127 |
| HART® - Common Practice Command Specification | 8.0 | HCF_SPEC-151 |
| HART® - Common Tables | 16.0 | HCF_SPEC-183 |
| Appendix 1 - Command Specific Response Code Definitions | 5.0 | HCF_SPEC-307 |
| Application Layer Guideline on HART Status Information | 1.0 | HCF_LIT-5 |

| | | |
|-------|---|-----|
| 01-01 | Abgeleitet aus Dokument „StratosPro A211-A411 CC HART CMD Spec 01-01.doc“, dabei alle bisherigen Änderungen im Dokument angenommen. | mes |
| 02-01 | Neue Parameter für Unterstützung von Kationentauscher | rth |
| | | |
| | | |
| | | |
| | | |

Content

| | | |
|------|--|----|
| 1 | 1. Reference Documents | 1 |
| 2 | Common Tables Related to A211 CC and A411 CC | 5 |
| 2.1 | Device Variable Code Tables | 5 |
| 2.2 | Analog Channel Code Table..... | 5 |
| 2.3 | Device Specific Unit Codes Table..... | 5 |
| 3 | Universal Commands | 6 |
| 3.1 | Command 0 Read Unique Identifier..... | 6 |
| 3.2 | Command 1 Read Primary Variable | 6 |
| 3.3 | Command 2 Read Loop Current and Percent of Range | 7 |
| 3.4 | Command 3 Read Dynamic Variables and Loop Current..... | 7 |
| 3.5 | Command 6 Write Polling Address | 8 |
| 3.6 | Command 7 Read Loop Configuration | 8 |
| 3.7 | Command 8 Read Dynamic Variable Classifications..... | 9 |
| 3.8 | Command 9 Read Device Variables with Status | 9 |
| 3.9 | Command 11 Read Unique Identifier Associated with Tag..... | 10 |
| 3.10 | Command 12 Read Message | 10 |
| 3.11 | Command 13 Read Tag, Descriptor, Date..... | 10 |
| 3.12 | Command 14 Read Primary Variable Transducer Information | 11 |
| 3.13 | Command 15 Read Device Information..... | 11 |
| 3.14 | Command 16 Read Final Assembly Number..... | 12 |
| 3.15 | Command 17 Write Message | 12 |
| 3.16 | Command 18 Write Tag, Descriptor, Date..... | 12 |
| 3.17 | Command 19 Write Final Assembly Number..... | 13 |
| 3.18 | Command 20 Read Long Tag..... | 13 |
| 3.19 | Command 21 Read Unique Identifier Associated With Long Tag | 13 |
| 3.20 | Command 22 Write Long Tag..... | 14 |
| 4 | Common Practice Commands | 15 |
| 4.1 | Command 33 Read Device Variables | 15 |
| 4.2 | Command 35 Write Primary Variable Range Values | 16 |
| 4.3 | Command 36 Set Primary Variable Upper Range Value | 16 |
| 4.4 | Command 37 Set Primary Variable Lower Range Value | 17 |
| 4.5 | Command 38 Reset Configuration Changed Flag | 17 |
| 4.6 | Command 41 Perform Self Test | 17 |
| 4.7 | Command 42 Perform Device Reset | 18 |
| 4.8 | Command 44 Write Primary Variable Units | 18 |
| 4.9 | Command 47 Write Primary Variable Transfer Function | 18 |
| 4.10 | Command 48 Read Additional Device Status | 19 |
| 4.11 | Command 50 Read Dynamic Variable Assignment..... | 20 |
| 4.12 | Command 53 Write Device Variable Units..... | 20 |
| 4.13 | Command 54 Read Device Variable Information..... | 21 |
| 4.14 | Command 59 Write Number of Response Preambles | 21 |
| 4.15 | Command 60 Read Analog Channel and Percent of Range | 22 |
| 4.16 | Command 62 Read Analog Channels | 22 |
| 4.17 | Command 63 Read Analog Channel Information | 23 |
| 4.18 | Command 64 Write Analog Channel Additional Damping Value | 23 |
| 4.19 | Command 65 Write Analog Channel Range Values | 24 |
| 4.20 | Command 69 Write Analog Channel Transfer Function | 24 |
| 4.21 | Command 71 Lock Device..... | 25 |
| 4.22 | Command 72 Squawk | 25 |
| 4.23 | Command 73 Find Device | 26 |
| 4.24 | Command 76 Read Lock Device State | 26 |
| 5 | Device Specific Commands..... | 27 |
| 5.1 | Command 128 Read Device Configuration | 27 |
| 5.2 | Command 135 Read Sensor Information | 28 |
| 5.3 | Command 136 Write Sensor Information..... | 28 |
| 5.4 | Command 137 Read Meas Mode | 29 |
| 5.5 | Command 138 Write Meas Mode | 30 |
| 5.1 | Command 143 Read Cation Exchanger | 31 |

| | | |
|------|--|----|
| 5.2 | Command 144 Write Cation Exchanger | 31 |
| 5.3 | Command 147 Read OUT1/OUT2..... | 32 |
| 5.4 | Command 148 Write OUT1/OUT2 | 33 |
| 5.5 | Command 159 Read Control Input | 33 |
| 5.6 | Command 160 Write Control Input | 34 |
| 5.7 | Command 161 Read Alarm | 34 |
| 5.8 | Command 162 Write Alarm..... | 35 |
| 5.9 | Command 165 Read MinMax | 35 |
| 5.10 | Command 166 Write MinMax | 36 |
| 5.11 | Command 173 Read Clock..... | 37 |
| 5.12 | Command 174 Write Clock..... | 37 |
| 5.13 | Command 175 Read Logbook Entry..... | 38 |
| 5.14 | Command 179 Read Cell Factor | 39 |
| 5.15 | Command 183 Read Device Tag..... | 39 |
| 5.16 | Command 184 Write Device Tag..... | 39 |
| 5.17 | Command 186 Read Unit Code..... | 40 |
| 5.18 | Command 187 Read Version Info..... | 40 |
| 5.19 | Command 189 Read Process Values..... | 41 |
| 5.20 | Command 191 Read Last Calibration Date | 42 |
| 5.21 | Command 193 Write TV and QV Assignment..... | 42 |
| 5.22 | Command 201 New Exchanger..... | 42 |

2 Common Tables Related to A211 CC and A411 CC

2.1 Device Variable Code Tables

| Device Variable Code | Measurement Value | Units Code | Lower Limit | Upper Limit | Minimum Span | Damping |
|----------------------|-------------------------------------|--------------------|-------------|-------------|--------------|---------|
| 0 | Conductivity A | 67 – uS/cm | 0 | 9999 | 0,0005 | 0 |
| 1 | Specific Resistance A | 245 – MOhm * cm | 0 | 99.99 | 0,005 | 0 |
| 2 | Temperature A | 32 – °C 33 – °F | -50 -58 | 200 392 | 0,05 0,09 | 0 |
| 3 | Conductivity B | 67 – uS/cm | 0 | 9999 | 0,0005 | 0 |
| 4 | Specific Resistance B | 245 – MOhm * cm | 0 | 99.99 | 0,005 | 0 |
| 5 | Temperature B | 32 – °C 33 – °F | -50 -58 | 200 392 | 0,05 0,09 | 0 |
| 6 | Difference | 67 – uS/cm | -1999 | 9999 | 0,05 | 0 |
| 7 | Ratio | 251 – none | 0 | 19.99 | 0,005 | 0 |
| 8 | Passage | 57 – % | 0 | 199.9 | 0,05 | 0 |
| 9 | Rejection | 57 – % | -199.9 | 199.9 | 0,05 | 0 |
| 10 | Deviation | 57 – % | -199.9 | 199.9 | 0,05 | 0 |
| 11 | pH (VBG 450) | 59 – pH | -2 | 16 | 0,005 | 0 |
| 12 | pH (variable) | 59 – pH | -2 | 16 | 0,005 | 0 |
| 13 | User spec (DAC) | 67 – uS/cm | 0 | 9999 | 0,05 | 0 |
| 14 | Concentration of alkalis medium(C9) | 139 – ppm | 0 | 99.99 | 0,05 | 0 |

| Device Variable Code | Device Variable | Device Variable Class | Device Variable Family |
|----------------------|-------------------------------------|-----------------------|------------------------|
| 0 | Conductivity A | 81 – Analytical | 250 – not used |
| 1 | Specific Resistance A | 64 – Temperature | 250 – not used |
| 2 | Temperature A | 81 – Analytical | 4 – Temperature |
| 3 | Conductivity B | 81 – Analytical | 250 – not used |
| 4 | Specific Resistance B | 81 – Analytical | 250 – not used |
| 5 | Temperature B | 64 – Temperature | 4 – Temperature |
| 6 | Difference | 81 – Analytical | 250 – not used |
| 7 | Ratio | 81 – Analytical | 250 – not used |
| 8 | Passage | 81 – Analytical | 250 – not used |
| 9 | Rejection | 81 – Analytical | 250 – not used |
| 10 | Deviation | 81 – Analytical | 250 – not used |
| 11 | pH (VBG 450) | 81 – Analytical | 8 – pH |
| 12 | pH (variable) | 81 – Analytical | 8 – pH |
| 13 | User spec (DAC) | 81 – Analytical | 250 – not used |
| 14 | Concentration of alkalis medium(C9) | 81 – Analytical | 250 – not used |

2.2 Analog Channel Code Table

| Analog Channel Code | Current Loop of Device |
|---------------------|-------------------------------|
| 0 | Primary Current Loop (OUT1) |
| 1 | Secondary Current Loop (OUT2) |

2.3 Device Specific Unit Codes Table

| Unit Code | Unit |
|-----------|-----------|
| 244 | 1/cm |
| 245 | MOhm * cm |

3 Universal Commands

3.1 Command 0 Read Unique Identifier

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|-------------|---|
| 0 | Unsigned-8 | (=254) |
| 1 | Enum | Manufacturer Identification Code (=97 for Knick) |
| 2 | Enum | Device Type (=0xD1 for A402 CC) |
| 3 | Unsigned-8 | Minimum Number of Preambles (=5) |
| 4 | Unsigned-8 | Universal Command Major Revision Number (=6) |
| 5 | Unsigned-8 | Device Revision Level (=4) |
| 6 | Unsigned-8 | Software Revision Level (=1) |
| 7 | Enum | Hardware Revision Level (=1) |
| 8 | Bits | Flags (=0) |
| 9-11 | Unsigned-24 | Device Identification Number |
| 12 | Unsigned-8 | Number of Preambles |
| 13 | Unsigned-8 | Maximum Number of Device Variables (=14, <i>Index of last device variable</i>) |
| 14-15 | Unsigned-16 | Configuration Change Counter |
| 16 | Bits | Extended Field Device Status |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.2 Command 1 Read Primary Variable

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Primary Variable Units Code (Coding see 2.1) |
| 1-4 | Float | Primary Variable |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.3 Command 2 Read Loop Current and Percent of Range

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------------|
| 0-3 | Float | Primary Variable Loop Current [mA] |
| 4-7 | Float | Primary Variable Percent of Range [%] |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.4 Command 3 Read Dynamic Variables and Loop Current

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|--------|---|
| 0-3 | Float | Primary Variable Loop Current [mA] |
| 4 | Enum | Primary Variable Units Code (Coding see 2.1) |
| 5-8 | Float | Primary Variable |
| 9 | Enum | Secondary Variable Units Code (Coding see 2.1) |
| 10-13 | Float | Secondary Variable |
| 14 | Enum | Tertiary Variable Units Code (Coding see 2.1) |
| 15-18 | Float | Tertiary Variable |
| 19 | Enum | Quaternary Variable Units Code (Coding see 2.1) |
| 20-23 | Float | Quaternary Variable |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.5 Command 6 Write Polling Address

Request Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Polling Address of Device |
| 1 | Enum | Loop Current Mode 0 – Disabled (= Multidrop Mode) 1 – Enabled (= Current Signaling Mode) |

Response Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Polling Address of Device |
| 1 | Enum | Loop Current Mode (Coding see Request) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|---|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Polling Address Selection (>63) |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

3.6 Command 7 Read Loop Configuration

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Polling Address of Device |
| 1 | Enum | Loop Current Mode (Coding see Command 6) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.7 Command 8 Read Dynamic Variable Classifications

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0 | Enum | Primary Variable Classification (Coding see 2.1) |
| 1 | Enum | Secondary Variable Classification (Coding see 2.1) |
| 2 | Enum | Tertiary Variable Classification (=250, <i>not supported</i>) |
| 3 | Enum | Quaternary Variable Classification (=250, <i>not supported</i>) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

Command 9 Read Device Variables with Status

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Slot 0: Device Variable Code (Coding see 2.1) |
| 1 | Unsigned-8 | Slot 1: Device Variable Code (Coding see 2.1) |
| 2 | Unsigned-8 | Slot 2: Device Variable Code (Coding see 2.1) |
| 3 | Unsigned-8 | Slot 3: Device Variable Code (Coding see 2.1) |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|--|
| 0 | Enum | Extended Field Device Status |
| 1 | Unsigned-8 | Slot 0: Device Variable Code (Coding see 2.1) |
| 2 | Enum | Slot 0: Device Variable Classification |
| 3 | Enum | Slot 0: Units Code |
| 4-7 | Float | Slot 0: Device Variable Value |
| 8 | Bits | Slot 0: Device Variable Status 0x00 – Bad 0x40 – Poor 0x80 – Good |
| 9 | Unsigned-8 | Slot 1: Device Variable Code |
| 10 | Enum | Slot 1: Device Variable Classification |
| 11 | Enum | Slot 1: Units Code |
| 12-15 | Float | Slot 1: Device Variable Value |
| 16 | Bits | Slot 1: Device Variable Status (Coding see Byte 8) |
| 17 | Unsigned-8 | Slot 2: Device Variable Code |
| 18 | Enum | Slot 2: Device Variable Classification |
| 19 | Enum | Slot 2: Units Code |
| 20-23 | Float | Slot 2: Device Variable Value |
| 24 | Bits | Slot 2: Device Variable Status (Coding see Byte 8) |
| 25 | Unsigned-8 | Slot 3: Device Variable Code |
| 26 | Enum | Slot 3: Device Variable Classification |
| 27 | Enum | Slot 3: Units Code |
| 28-31 | Float | Slot 3: Device Variable Value |
| 32 | Bits | Slot 3: Device Variable Status (Coding see Byte 8) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 8 | Warning | Update Failure |

Command 11 Read Unique Identifier Associated with Tag

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| 0-5 | Packed | Tag |

Response Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0-16 | | Same as Command 0 (Read Unique Identifier) No response is made unless the Tag matches that of the device. |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.10 Command 12 Read Message

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| 0-23 | Packed | Message |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.11 Command 13 Read Tag, Descriptor, Date

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|--------|-------------|
| 0-5 | Packed | Tag |
| 6-17 | Packed | Descriptor |
| 18-20 | Date | Date Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.12 Command 14 Read Primary Variable Transducer Information

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|-------------|---|
| 0-2 | Unsigned-24 | Numerical Sensor Serialnumber - ISM sensors only (reads 0 if there is no ISM sensor) |
| 3 | Enum | Transducer Limits and Minimum Span Units Code (Coding see 2.1) |
| 4-7 | Float | Upper Transducer Limit |
| 8-11 | Float | Lower Transducer Limit |
| 12-15 | Float | Minimum Span |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.13 Command 15 Read Device Information

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|--------|---|
| 0 | Enum | PV Alarm Selection Code 0 – High 239 – Last Val |
| 1 | Enum | PV Transfer Function Code (=0, linear) |
| 2 | Enum | PV Upper and Lower Range Values Units Code (Coding see 2.1) |
| 3-6 | Float | PV Upper Range Value |
| 7-10 | Float | PV Lower Range Value |
| 11-14 | Float | PV Damping Value [s] |
| 15 | Enum | Write Protect Code (=251, None) |
| 16 | Enum | Private Label Distributor Code (=97, Knick) |
| 17 | Bits | PV Analog Channel Flags (=0) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.14 Command 16 Read Final Assembly Number

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|-------------|-----------------------|
| 0-2 | Unsigned-24 | Final Assembly Number |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.15 Command 17 Write Message

Request Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0-23 | Packed | Message String Used by the Master for Record Keeping |

Response Data Bytes

| Byte | Format | Description |
|------|--------|----------------|
| 0-23 | Packed | Message String |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

Command 18 Write Tag, Descriptor, Date

Request Data Bytes

| Byte | Format | Description |
|-------|-------------|--|
| 0-5 | Packed | Tag |
| 6-17 | Packed | Descriptor Used by the Master for Record Keeping |
| 18-20 | Unsigned-24 | A Date Code Used by the Master for Record Keeping (e.g. Last Or Next Calibration Date) |

Response Data Bytes

| Byte | Format | Description |
|-------|--------|-------------|
| 0-5 | Packed | Tag |
| 6-17 | Packed | Descriptor |
| 18-20 | Date | Date Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 9 | Error | Invalid Date Code Detected |
| 16 | Error | Access Restricted |

3.17 Command 19 Write Final Assembly Number

Request Data Bytes

| Byte | Format | Description |
|------|-------------|-----------------------|
| 0-2 | Unsigned-24 | Final Assembly Number |

Response Data Bytes

| Byte | Format | Description |
|------|-------------|-----------------------|
| 0-2 | Unsigned-24 | Final Assembly Number |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

3.18 Command 20 Read Long Tag

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|---------|-------------|
| 0-31 | Latin-1 | Long Tag |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.19 Command 21 Read Unique Identifier Associated With Long Tag

Request Data Bytes

| Byte | Format | Description |
|------|---------|-------------|
| 0-31 | Latin-1 | Long Tag |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0-16 | | Same as Command 0 (Read Unique Identifier) No response is made unless the Long Tag matches that of the device. |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

3.20 Command 22 Write Long Tag

Request Data Bytes

| Byte | Format | Description |
|------|---------|-------------|
| 0-31 | Latin-1 | Long Tag |

Response Data Bytes

| Byte | Format | Description |
|------|---------|-------------|
| 0-31 | Latin-1 | Long Tag |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

4 Common Practice Commands

4.1 Command 33 Read Device Variables

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Slot 0: Device Variable Code (Coding see 2.1) |
| 1 | Unsigned-8 | Slot 1: Device Variable Code (Coding see 2.1) |
| 2 | Unsigned-8 | Slot 2: Device Variable Code (Coding see 2.1) |
| 3 | Unsigned-8 | Slot 3: Device Variable Code (Coding see 2.1) |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|-------------------------------------|
| 0 | Unsigned-8 | Slot 0: Device Variable Code |
| 1 | Enum | Slot 0: Units Code (Coding see 2.1) |
| 2-5 | Float | Slot 0: Device Variable Value |
| 6 | Unsigned-8 | Slot 1: Device Variable Code |
| 7 | Enum | Slot 1: Units Code (Coding see 2.1) |
| 8-11 | Float | Slot 1: Device Variable Value |
| 12 | Unsigned-8 | Slot 2: Device Variable Code |
| 13 | Enum | Slot 2: Units Code (Coding see 2.1) |
| 14-17 | Float | Slot 2: Device Variable Value |
| 18 | Unsigned-8 | Slot 3: Device Variable Code |
| 19 | Enum | Slot 3: Units Code (Coding see 2.1) |
| 20-23 | Float | Slot 3: Device Variable Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 8 | Warning | Update Failure |

4.2 Command 35 Write Primary Variable Range Values

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Upper and Lower Range Values Units Code (must be the same as the actually used unit) (Coding see 2.1) |
| 1-4 | Float | Upper Range Value |
| 5-8 | Float | Lower Range Value |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Upper and Lower Range Values Units Code |
| 1-4 | Float | Upper Range Value |
| 5-8 | Float | Lower Range Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 9 | Error | Lower Range Value Too High |
| 10 | Error | Lower Range Value Too Low |
| 11 | Error | Upper Range Value Too High |
| 12 | Error | Upper Range Value Too Low |
| 16 | Error | Access Restricted |
| 29 | Error | Invalid Span |

4.3 Command 36 Set Primary Variable Upper Range Value

This command sets the actual value of the Primary Variable as the Upper Range Value.

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 9 | Error | Applied Process Too High |
| 10 | Error | Applied Process Too Low |
| 16 | Error | Access Restricted |
| 29 | Error | Invalid Span |

4.4 Command 37 Set Primary Variable Lower Range Value

This Command sets the actual value of the Primary Variable as the Lower Range Value.

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 9 | Error | Applied Process Too High |
| 10 | Error | Applied Process Too Low |
| 16 | Error | Access Restricted |
| 29 | Error | Invalid Span |

4.5 Command 38 Reset Configuration Changed Flag

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 16 | Error | Access Restricted |

4.6 Command 41 Perform Self Test

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 16 | Error | Access Restricted |

4.7 Command 42 Perform Device Reset

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 16 | Error | Access Restricted |

4.8 Command 44 Write Primary Variable Units

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Primary Variable Units Code (switching between °C and °F is allowed, all other units must not be changed) |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-----------------------------|
| 0 | Enum | Primary Variable Units Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

4.9 Command 47 Write Primary Variable Transfer Function

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------------------------------|
| 0 | Enum | Transfer Function Code (=0, linear) |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------------------------------|
| 0 | Enum | Transfer Function Code (=0, linear) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

4.10 Command 48 Read Additional Device Status

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|--|
| 0 | Unsigned-8 | Error number |
| 1 | Unsigned-8 | Reserved |
| 2 | Enum | Device Specific Status: 0 – MEAS 1 – DIAG 2 – CAL 3 – CONF 4 – SERVICE |
| 3 | Enum | Sensoface: 0 – Good 1 – Poor 2 – Bad 3 – Unknown |
| 4 | Enum | Reserved |
| 5 | Bits | State: 0x10 – Alarm 0x08 – Sensors Connected 0x01 – Hold |
| 6 | Bits | Extended Device Status: 0x01 – Maintenance required |
| 7-9 | Bits | Reserved |
| 10 | Bits | Analog Channel Saturation: 0x02 – Channel 2 saturated 0x01 – Channel 1 saturated |
| 11-12 | Bits | Reserved |
| 13 | Bits | Analog Channel Fixed: 0x02 – Channel 2 fixed 0x01 – Channel 1 fixed |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

4.11 Command 50 Read Dynamic Variable Assignment

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Device Variable assigned to the Primary Variable (Coding see 2.1) |
| 1 | Unsigned-8 | Device Variable assigned to the Secondary Variable (Coding see 2.1) |
| 2 | Unsigned-8 | Device Variable assigned to the Tertiary Variable (=250, <i>not used</i>) |
| 3 | Unsigned-8 | Device Variable assigned to the Quaternary Variable (=250, <i>not used</i>) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

4.12 Command 53 Write Device Variable Units

Request Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Device Variable Code (Coding see 2.1) |
| 1 | Enum | Device Variable Units Code (switching between °C and °F is allowed, all other units must not be changed) |

Response Data Bytes

| Byte | Format | Description |
|------|------------|----------------------------|
| 0 | Unsigned-8 | Device Variable Code |
| 1 | Enum | Device Variable Units Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|------------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 11 | Error | Unvalid Device Variable Code |
| 12 | Error | Invalid Units Code |
| 16 | Error | Access Restricted |

4.13 Command 54 Read Device Variable Information

Request Data Bytes

| Byte | Format | Description |
|------|------------|----------------------|
| 0 | Unsigned-8 | Device Variable Code |

Response Data Bytes

| Byte | Format | Description |
|-------|-------------|---|
| 0 | Unsigned-8 | Device Variable Code |
| 1-3 | Unsigned-24 | Device Variable Transducer Serialnumber (ISM sensors only) |
| 4 | Enum | Device Variable Limits/Minimum Span Units Code (Coding see 2.1) |
| 5-8 | Float | Device Variable Upper Transducer Limit |
| 9-12 | Float | Device Variable Lower Transducer Limit |
| 13-16 | Float | Device Variable Damping Value (=0) |
| 17-20 | Float | Device Variable Minimum Span |
| 21 | Enum | Device Variable Classification (Coding see 2.1) |
| 22 | Enum | Device Variable Family (Coding see 2.1) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

4.14 Command 59 Write Number of Response Preambles

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Number of preambles to be sent with the response message from Slave to the Master |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Number of preambles to be sent with the response message from Slave to the Master |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 8 | Warning | Set to Nearest Possible Value |
| 16 | Error | Access Restricted |

4.15 Command 60 Read Analog Channel and Percent of Range

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code (Coding see 2.2) |

Response Data Bytes

| Byte | Format | Description |
|------|------------|-------------------------------------|
| 0 | Unsigned-8 | Analog Channel Number Code |
| 1 | Enum | Analog Channel Units Code (=39, mA) |
| 2-5 | Float | Analog Channel Level |
| 6-9 | Float | Analog Channel Percent of Range |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

4.16 Command 62 Read Analog Channels

Request Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Analog Channel Number Code assigned to Slot 0 (Coding see 2.2) |
| 1 | Unsigned-8 | Analog Channel Number Code assigned to Slot 1 (Coding see 2.2) |
| 2 | Unsigned-8 | Analog Channel Number Code assigned to Slot 2 (Coding see 2.2) |
| 3 | Unsigned-8 | Analog Channel Number Code assigned to Slot 3 (Coding see 2.2) |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code in Slot 0 |
| 1 | Enum | Slot 0 Units Code (=39, mA) |
| 2-5 | Float | Slot 0 Level of selected Analog Channel |
| 6 | Unsigned-8 | Analog Channel Number Code in Slot 1 |
| 7 | Enum | Slot 1 Units Code (=39, mA) |
| 8-11 | Float | Slot 1 Level of selected Analog Channel |
| 12 | Unsigned-8 | Analog Channel Number Code in Slot 2 |
| 13 | Enum | Slot 2 Units Code (=39, mA) |
| 14-17 | Float | Slot 2 Level of selected Analog Channel |
| 18 | Unsigned-8 | Analog Channel Number Code in Slot 3 |
| 19 | Enum | Slot 3 Units Code (=39, mA) |
| 20-23 | Float | Slot 3 Level of selected Analog Channel |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

4.17 Command 63 Read Analog Channel Information

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code (Coding see 2.2) |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code |
| 1 | Enum | Analog Channel Alarm Selection Code 0 – High 239 – Last Val |
| 2 | Enum | Analog Channel Transfer Function Code (=0, linear) |
| 3 | Enum | Analog Channel Upper and Lower Range Values Units Code (Coding see 2.1) |
| 4-7 | Float | Analog Channel Upper Range Value |
| 8-11 | Float | Analog Channel Lower Range Value |
| 12-15 | Float | Analog Channel Damping Value [s] |
| 16 | Bits | Analog Channel Flags (=0) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

4.18 Command 64 Write Analog Channel Additional Damping Value

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code (Coding see 2.2) |
| 1-4 | Float | Analog Channel Additional Damping Value [s] |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code |
| 6-9 | Float | Analog Channel Additional Damping Value [s] |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

4.19 Command 65 Write Analog Channel Range Values

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code (Coding see 2.2) |
| 1 | Enum | Analog Channel Upper and Lower Range Values Units Codes (the actually used unit must not be changed) (Coding see 2.1) |
| 2-5 | Float | Analog Channel Upper Range Value |
| 6-9 | Float | Analog Channel Lower Range Value |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Analog Channel Number Code |
| 1 | Enum | Analog Channel Upper and Lower Range Values Units Codes |
| 2-5 | Float | Analog Channel Upper Range Value |
| 6-9 | Float | Analog Channel Lower Range Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|------------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Error Code |
| 9 | Error | Lower Range Value Too High |
| 10 | Error | Lower Range Value Too Low |
| 11 | Error | Upper Range Value Too High |
| 12 | Error | Upper Range Value Too Low |
| 15 | Error | Invalid Analog Channel Code Number |
| 16 | Error | Access Restricted |
| 29 | Error | Invalid Span |

4.20 Command 69 Write Analog Channel Transfer Function

Request Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Analog Channel Number Code (Coding see 2.2) |
| 1 | Enum | Analog Channel Transfer Function Code (=0, linear) |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---------------------------------------|
| 0 | Unsigned-8 | Analog Channel Number Code |
| 1 | Enum | Analog Channel Transfer Function Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|------------------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 13 | Error | Invalid Transfer Function Code |
| 15 | Error | Invalid Analog Channel Code Number |
| 16 | Error | Access Restricted |

4.21 Command 71 Lock Device

Request Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0 | Enum | Lock Code: 0 – Unlocked 1 – Lock – Temporary 2 – Lock – Permanent |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| 0 | Enum | Lock Code |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 10 | Error | Invalid Lock Code |
| 16 | Error | Access Restricted |

4.22 Command 72 Squawk

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

4.23 Command 73 Find Device

The A211 Cond / A411 Cond must be set to Diag mode manually before using this command. In all other modes the device will not answer this command.

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0-16 | Bits | Same as Command 0 (Read Unique Identifier) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

4.24 Command 76 Read Lock Device State

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Bits | Lock Status: 0x01 – Device Locked 0x02 – Lock is Permanent 0x04 – Locked by Primary Master |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5 Device Specific Commands

5.1 Command 128 Read Device Configuration

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Bits | 0x01 – 1= A402 CC 0x04 – 0= non Ex, 1= Ex 0x08 – 1= Option Secondary Loop Current activated 0x20 – 1= Option Logbook activated 0x40 – 1= Option Current Input activated |
| 1 | Bits | 0x01 – 1= Option Audit Trail activated |
| 2 | Unsigned-8 | Reserved |
| 3 | Unsigned-8 | Reserved |

5.2 Command 135 Read Sensor Information

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Sensor selection: 0 – Sensor A 1 – Sensor B |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|------|--------|---|---------------------------|
| 0 | Enum | Sensor selection | |
| 1-4 | Float | Cellfactor [1/cm] | S_A / S_B: CELLFACTOR |
| 5 | Enum | TC Type: 0 – OFF 1 – LIN 2 – NLF 3 – nACL 4 – HCL 5 – nH3 6 – nAOH | S_A / S_B: TC SELECT |
| 6-9 | Float | TC Liquid [%/K] | S_A / S_B: TC LIQUID |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.3 Command 136 Write Sensor Information

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-9 | | Same as Response of Command 135 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-9 | | Same as Response of Command 135 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.4 Command 137 Read Meas Mode

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| 0 | Enum | (=0) |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|-------|--------|---|---------------------------|
| 0 | Enum | (=0) | |
| 1 | Enum | Meas Range: 0 – 0.000 µS/cm 1 – 00.00 µS/cm 2 – 000.0 µS/cm 3 – 0000 µS/cm 4 – 00.00 MΩ*cm | MES: MEAS RANGE |
| 2 | Enum | Temperature Unit: 32 – °C 33 – °F | MES: TEMP UNIT |
| 3 | Enum | Calculation: 0 – OFF 1 – ON | MES: CALCULATION |
| 4 | Enum | Calculation Type: 0 – C1: Difference 1 – C2: Ratio 2 – C3: Passage 3 – C4: Rejection 4 – C5: Deviation 5 – C6: pH (VGB) 6 – C7: pH (variable) 7 – C8: User Spec (DAC) 8 – C9: Alkalising | MES: |
| 5-8 | Float | Factor 1 (C7 only) | C7: FACTOR 1 |
| 9-12 | Float | Factor 2 (C7 only) | C7: FACTOR 2 |
| 13-16 | Float | Parameter W [10 ⁻³] (C8 only) | C8: PARAMETER W |
| 17-20 | Float | Parameter A [10 ⁻³] (C8 only) | C8: PARAMETER A |
| 21-24 | Float | Parameter B [10 ⁻⁴] (C8 only) | C8: PARAMETER B |
| 25 | Enum | Solution for Calculation (C6 and C9) 0: NaOH 1: NH3 2: LiOH | C6/9: |
| 26-29 | Float | Coefficient for Calculation (C7 only) | C7: COEFFICIENT |
| 30-33 | Float | Factor 3 (C7 only) | C7: FACTOR 3 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.5 Command 138 Write Meas Mode

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-33 | | Same as Response of Command 137 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-33 | | Same as Response of Command 137 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

Command 143 Read Cation Exchanger

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|------|--------|---|---------------------------|
| 0 | Enum | Exchanger Capacity Calculation (C6 only) 0 – OFF 1 – ON | C6: EXCHER CAP |
| 1-4 | Float | Exchanger Size [l] (C6 only) | C6: EXCHER SIZE |
| 5-8 | Float | Capacity [val] (C6 only) | C6: CAPACITY |
| 9-12 | Float | Efficiency [%] (C6 only) | C6: EFFICIENCY |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5.2 Command 144 Write Cation Exchanger

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-12 | | Same as Response of Command 143 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-12 | | Same as Response of Command 143 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.3 Command 147 Read OUT1/OUT2

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Analog channel selection: 0 – OUT1 1 – OUT2 |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|-------|--------|--|---------------------------|
| 0 | Enum | Analog channel selection | |
| 1 | Enum | Channel: 0 – Conductivity Sensor A (COND A) 1 – Conductivity Sensor B (COND B) 2 – Temperature Sensor A (TMP A) 3 – Temperature Sensor B (TMP B) 4 – Calculation (CALC) | OT1/2: CHANNEL |
| 2 | Enum | Output Range: 0 – 0-20mA 1 – 4-20mA | OT1/2: RANGE |
| 3 | Enum | Output: 0 – linear (LIN) 2 – bilinear (BI LIN) | OT1/2: OUTPUT |
| 4-7 | Float | BEGIN Value | OT1/2: BEGIN |
| 8-11 | Float | END Value | OT1/2: END |
| 12-15 | Float | Filtertime [s] | OT1/2: FILTERTIME |
| 16 | Enum | 22mA-Fail: 0 – OFF 1 – ON | OT1/2: 22mA-FAIL |
| 17 | Enum | Hold Mode: 1 – FIX 2 – LAST | OT1/2: HOLD MODE |
| 18-21 | Float | Hold Fix | OT1/2: HOLD FIX |
| 22-25 | Float | Corner X for Output = BI LIN | OT1/2: CORNER X |
| 26-29 | Float | Corner Y for Output = BI LIN | OT1/2: CORNER Y |
| 30 | Enum | 22mA on Sensoface Message: 0 – OFF 1 – ON | OT1/2: FACE 22mA |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.4 Command 148 Write OUT1/OUT2

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-30 | | Same as Response of Command 147 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-30 | | Same as Response of Command 147 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.5 Command 159 Read Control Input

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|------|--------|---------------------------------------|---------------------------|
| 0 | Enum | Control Mode 0 – LEVEL 1 – FLOW | IN: CONTROL |
| 1-4 | Float | Adjust Flow for Control Mode = Flow | IN: ADJUST FLOW |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5.6 Command 160 Write Control Input

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-4 | | Same as Response of Command 159 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-4 | | Same as Response of Command 159 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.7 Command 161 Read Alarm

Request Data Bytes

| Format | Description |
|--------|-------------|
| 0 | Enum (=0) |

Response Data Bytes

| Format | Description | Parameter Name on Display |
|--------|-------------|--|
| 0 | Enum (=0) | |
| 1-4 | Float | Delay Time [s] |
| 5 | Enum | Sensocheck: 0 – OFF 1 – ON |
| 6 | Enum | Control Input: 0 – OFF 1 – ON |
| 7-10 | Float | Flow Min [l/h] |
| 11-14 | Float | Flow Max [l/h] |
| 15 | Enum | Limit I-Input: 0 – OFF 1 – ON |
| 16 | Enum | Function: 0 – Low Level 1 – High Level |
| 17-20 | Float | Level [mA] |
| 21-24 | Float | Hysteresis [mA] |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.8 Command 162 Write Alarm

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-24 | | Same as Response of Command 161 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-24 | | Same as Response of Command 161 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.9 Command 165 Read MinMax

Request Data Bytes

| Byte | Format | Description |
|------|--------|--|
| 0 | Enum | Relais and analog channel selection: 0 – Rel1 1 – Rel2 2 – Rel3 |

Response Data Bytes

| Byte | Format | Description | Parameter Name on Display |
|-------|--------|---|---------------------------|
| 0 | Enum | Relais and analog channel selection | |
| 1 | Enum | Channel: 0 – Conductivity Sensor A (COND A) 1 – Conductivity Sensor B (COND B) 2 – Temperature Sensor A (TMP A) 3 – Temperature Sensor B (TMP B) 4 – Calculation (CALC) 5 – Control (FLOW) 6 – Input Current (I INPUT) | RL1/2/3: CHANNEL |
| 2 | Enum | Function: 0 – Low Level 1 – High Level | RL1/2/3: FUNCTION |
| 3 | Enum | Contact Type: 0 – N/O 1 – N/C | RL1/2/3: CONTACT |
| 4-7 | Float | Level | RL1/2/3: LEVEL |
| 8-11 | Float | Hysteresis | RL1/2/3: HYSTERESIS |
| 12-15 | Float | Delay Time [s] | RL1/2/3: DELAYTIME |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.10 Command 166 Write MinMax

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-15 | | Same as Response of Command 165 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-15 | | Same as Response of Command 165 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 3 | Error | Passed Parameter Too Large |
| 4 | Error | Passed Parameter Too Small |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

5.11 Command 173 Read Clock

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| | | None |

Response Data Bytes

| Byte | Format | Description |
|------|-------------|--------------|
| 0-1 | Unsigned-16 | Milliseconds |
| 2 | Unsigned-8 | Minute |
| 3 | Unsigned-8 | Hour |
| 4 | Unsigned-8 | Day |
| 5 | Unsigned-8 | Month |
| 6 | Unsigned-8 | Year |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5.12 Command 174 Write Clock

Request Data Bytes

| Byte | Format | Description |
|------|-------------|-------------------------|
| 0-1 | Unsigned-16 | Milliseconds (0..59999) |
| 2 | Unsigned-8 | Minute (0..59) |
| 3 | Unsigned-8 | Hour (0..23) |
| 4 | Unsigned-8 | Day (1..31) |
| 5 | Unsigned-8 | Month (1..12) |
| 6 | Unsigned-8 | Year (1..255) |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-6 | | Same as Response of Command 173 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 9 | Error | Invalid Date Code Detected |
| 16 | Error | Access Restricted |

Command 175 Read Logbook Entry

Request Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Unsigned-8 | Group index: Value range depends on setting of Logbook options No Logbook option activated: 0 Logbook activated: 0.. 49 Logbook + Audit Trail activated: 0.. 99 |

Response Data Bytes

| Byte | Format | Description |
|-------|------------|--|
| 0 | Unsigned-8 | Group Index |
| 1 | Unsigned-8 | Index of latest entry |
| 2 | Unsigned-8 | Index of the first entry of the requested group index |
| 3-27 | | Logbook entry |
| 28 | Unsigned-8 | Index of the second entry of the requested group index |
| 29-53 | | Logbook entry |

Logbook Entry

| Byte | Format | Description |
|-------|-------------|--|
| 0 | Unsigned-8 | Message ID |
| 1 | Unsigned-8 | Day |
| 2 | Unsigned-8 | Month |
| 3 | Unsigned-8 | Year |
| 4-9 | Packed | Time (Format: "hh:mm:ss") |
| 10 | Bits | Info Flag: 0x01 - 0x02: Sensoface 0 – Good 1 – Medium 2 – Bad 3 – Unknown 0x04: ParseT 0 – ParseT_A 1 – ParseT_B 0x08 - 0x10: Reserved 0x20 - 0x80: Kind of Message 0 – Static 1 – Begin of event 2 – End of event 3 – Float (Bytes 11-14 are valid, 15-18 are reserved) 4 – Unsigned-32 (Bytes 15-18 are valid, 11-14 and 19-24 are reserved) 5 – Packed (Bytes 19-24 are valid, 11-18 are reserved) |
| 11-14 | Float | Float Value |
| 15-18 | Unsigned-32 | Integer Value |
| 19-24 | Packed | String Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.14 Command 179 Read Cell Factor

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Sensor selection: 0 – Sensor A 1 – Sensor B |

Response Data Bytes

| Byte | Format | Description |
|------|------------|--|
| 0 | Enum | Sensor selection |
| 1 | Unsigned-8 | Result of the last calibration, Sensoface: 0 – Good 1 – Medium 2 – Bad 3 – Unknown |
| 2 | Unsigned-8 | Cell Factor Units Code (=244, 1/cm) |
| 3-6 | Float | Cell Factor Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

Command 183 Read Device Tag

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| | | None |

Response Data Bytes

| Byte | Format | Description |
|------|---------|-------------|
| 0-31 | Latin-1 | Device Tag |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5.16 Command 184 Write Device Tag

Request Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-31 | | Same as Response of Command 183 |

Response Data Bytes

| Byte | Format | Description |
|------|--------|---------------------------------|
| 0-31 | | Same as Response of Command 183 |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-------------------------------|
| 0 | Success | No Command-Specific Errors |
| 5 | Error | Too Few Data Bytes Received |
| 6 | Error | Device-Specific Command Error |
| 16 | Error | Access Restricted |

Command 186 Read Unit Code

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Analog channel selection: 0 – OUT1 1 – OUT2 |

Response Data Bytes

| Byte | Format | Description |
|------|------------|-----------------------------|
| 0 | Enum | Analog channel selection |
| 1 | Unsigned-8 | Units Code (Coding see 2.1) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

Command 187 Read Version Info

Request Data Bytes

| Byte | Format | Description |
|------|--------|---|
| 0 | Enum | Info Request Selector: 0 – Device: Software Version 1 – Device: Hardware Version 2 – Device: Serialnumber 4 – HART IF: Software Version 7 – Meas Unit: Software Version 8 – Meas Unit: Hardware Version 9 – Meas Unit: Serialnumber 16 – Device: Bootloader Version 17 – Meas Unit: Bootloader Version |

Response Data Bytes

| Byte | Format | Description |
|------|------------|-----------------------|
| 0 | Unsigned-8 | Info Request Selector |
| 1-24 | Latin-1 | Requested Information |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.19 Command 189 Read Process Values

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Info Request Selector: 0 – Sensor A: Resistance of Temperature Sensor [Ohm] 1 – Sensor A: Temperature [°C] or [°F] 2 – Sensor A: Resistance [Ohm] 3 – Sensor A: Conductance [uS] 4 – Sensor A: Conductivity temp. comp. [uS/cm] 5 – Sensor B: Resistance of Temperature Sensor [Ohm] 6 – Sensor B: Temperature [°C] or [°F] 7 – Sensor B: Resistance [Ohm] 8 – Sensor B: Conductance [uS] 9 – Sensor B: Conductivity temp. comp. [uS/cm] 10 – Current Input [mA] 11 – Flow [l/h] 12 – Remaining exchanger capacity [%] 13 – Concentration of alkalis media (C9) [ppm] |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Info Request Selector |
| 1 | Enum | Unit Codes: 32 – °C 33 – °F 37 – Ohm 39 – mA 56 – uS 57 – % 67 – uS/cm 138 – l/h 139 – ppm |
| 2-5 | Float | Process Value |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |

5.20 Command 191 Read Last Calibration Date

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|---------|--|
| 0..7 | Latin-1 | Date of latest calibration (Format „dd.mm.yy“) |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |

5.21 Command 193 Write TV and QV Assignment

Request Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Device Variable assigned to the Tertiary Variable |
| 1 | Unsigned-8 | Device Variable assigned to the Quaternary Variable |

Response Data Bytes

| Byte | Format | Description |
|------|------------|---|
| 0 | Unsigned-8 | Device Variable assigned to the Tertiary Variable |
| 1 | Unsigned-8 | Device Variable assigned to the Quaternary Variable |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|-----------------------------|
| 0 | Success | No Command-Specific Errors |
| 2 | Error | Invalid Selection |
| 5 | Error | Too Few Data Bytes Received |
| 16 | Error | Access Restricted |

5.22 Command 201 New Exchanger

Request Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Response Data Bytes

| Byte | Format | Description |
|------|--------|-------------|
| None | | |

Command-Specific Response Codes

| Code | Class | Description |
|------|---------|----------------------------|
| 0 | Success | No Command-Specific Errors |
| 16 | Error | Access Restricted |